



COOLING EQUIPMENT RENTAL SPECIFICATIONS **(12,000 Btu's thru 540,000 Btu's)**

PORTABLE AIR-COOLED AIR-CONDITIONING EQUIPMENT

Air-cooled portables rentals are available in different models, capacities, and voltages. Applications include mostly commercial and industrial environments where supplemental, permanent, backup or spot cooling rentals are required.

EQUIPMENT	CAPACITY (BTU'S)	VOLTAGE /PHASE	BREAKER AMPS	SOUND LEVEL	NEMA PLUG	DIMENSIONS W x D x H
PAC1211	11,800	115	15	54	5-15	20 x 25 x 37
2OAC1211	11,800	115	15	54	5-15	20 x 26.7 x 38.7
OP12	12,000	115	15	52	5-15	21 x 27 x 44
CPK12	12,000	115	15	53	5-15	22 x 27 x 47
CP14	13,200	115	15	57	5-15	19 x 26 x 41
CPX14	13,200	115	15	55	5-15	22 x 29 x 48
PAC1811	16,800	115	20	60	5-20	24 x 30 x 44.5
2OAC1811	16,800	115	20	60	5-20	24 x 31.5 x 46.7
CPK18	16,800	115	20	59	5-20	21 x 27 x 47
OP18	16,800	115	20	61	5-20	21 x 27 x 44
CPX20	16,800	115	20	62	5-20	22 x 29 x 51
PAC2412	24,020	208/230/1	20	65	6-20	24 x 30 x 44.5
2OAC2412	24,020	208/230/1	20	65	6-20	24 x 30 x 45.75
OP24	24,000	208/230/1	20	63	6-20	21 x 27 x 49
CPK24	24,000	208/230/1	20	61	6-20	22 x 27 x 51
CP26	24,000	208/230/1	20	66	6-20	19 x 29 x 47
CPX26	24,000	208/230/1	20	64	6-20	22 x 29 x 51



PH: (224)535-8363
 EMAIL: info@rent-ac.com
 WEBSITE: www.rent-ac.com



PORTABLE AIR-COOLED AIR-CONDITIONING EQUIPMENT (CONT.)

EQUIPMENT	CAPACITY (BTU'S)	VOLTAGE /PHASE	BREAKER AMPS	SOUND LEVEL	NEMA PLUG	DIMENSIONS W x D x H
PAC3612	36,050	208/230/1	30	69	6-30	27 x 35 x 50.25
PAC3632	36,050	208/230/3	30	69	L15-30	27 x 35 x 50.25
PAC3634	36,050	460/3	20	69	L16-20	27 x 35 x 50.25
2OAC3612	36,050	208/230/1	30	69	6-30	27.5 x 37 x 52.7
OP36	36,000	208/230/1	30	65	6-30	30 x 44 x 52
CPK36	36,000	208/230/1	30	66	6-30	31 x 55 x 53
2OAC3632	36,050	208/230/3	30	69	L15-30	27.5 x 37 x 52.7
2OAC3634	36,050	460/3	20	69	L16-20	27.5 x 37 x 52.7
PAC6012	60,100	208/230/1	50	78	6-50	27 x 39.5 x 51.3
PAC6032	60,100	208/230/3	30	78	L15-30	27 x 39.5 x 51.3
PAC6034	60,100	460/3	20	78	L16-20	27 x 39.5 x 51.3
2OAC6012	60,100	208/230/1	50	78	6-50	28.2 x 41 x 54.2
OP60	60,000	208/230/1	50	69	6-50	30 x 52 x 64
CPK60	60,000	208/230/1	50	67	6-50	31 x 55 x 64
2OAC6032	60,100	208/230/3	30	78	L15-30	28.2 x 41 x 54.2
2OAC6034	60,100	460/3	20	78	L16-20	28.2 x 41 x 54.2
OP63	60,000	460/3	20	67	L16-20	30 x 52 x 64
CPK63	60,000	460/3	20	67	L16-20	31 x 55 x 64





INDOOR/OUTDOOR RATED AIR-CONDITIONING EQUIPMENT RENTALS

Larger Equipment Rentals are often placed outside and ducted into space were needed. Power to larger equipment is achieved through cam-lock cables which tie into the main building power distribution panel or a generator. Outdoor AC equipment rentals range from a nominal 40,000 Btu's through 540,000 Btu's

EQUIPMENT	CAPACITY (BTU'S)	VOLTAGE /PHASE	BREAKER AMPS	DUCT SIZE		NEMA PLUG	DIMENSIONS W x D x H
				EVAP(#)	COND		
Classic 40	39,000	208/230/3	25	12"(1)	-	L15-30	26 x 43 x 38
Classic 60	60,000	460/3	20	12"(1)	-	WIRED	32 x 49 x 42

EQUIPMENT	CAPACITY(BTU'S)		VOLTAGE /PHASE	BREAKER AMPS	DUCT SIZE		NEMA PLUG	DIMENSIONS W x D x H
	COOLING	HEATING			EVAP(#)	COND(#)		
KPO0521	60,000	41,000	208/230/1	60/50	12"(2)	12"(1)	WIRED	32 x 48 x 49
KPO0523	60,000	41,000	208/230/3	50	12"(2)	12"(1)	WIRED	32 x 48 x 49
KPO0543	60,000	41,000	460/3	20	12"(2)	12"(1)	WIRED	32 x 48 x 49
KPO1223	135,000	82,000	208/230/3	80	12"(4)	20"(1)	CAM	32 x 64 x 52
KPO1243	135,000	82,000	460/3	40	12"(4)	20"(1)	CAM	32 x 64 x 52
PACH12W32	149,700	-	208/230/3	100	12"(4)	-	CAM	43 x 68 x 58
OPAC14432	144,000	OPT. KW	208/230/3	60	16"(4)	20"(2)	CAM	72 x 30 x 77
PACH12N32	144,000	OPT. KW	208/230/3	100	12"(4)	20"(1)	CAM	43 x 68 x 58
PACH12N34	144,000	OPT. KW	460/3	50	12"(4)	20"(1)	CAM	43 x 68 x 58
AC10HS34	144,000	-	460/3	50	12"(4)	20"	CAM	35 x 95.5 x 73
AC30HSH34	360,000	48 kW	460/3	125(MFS)	20"(3)	-	CAM	72 x 97 x 98.3
SHCP48A-HS	540,000	-	460/3	125(MFS)	20"(4)	-	CAM	96 x 88 x 99.8





WATER-COOLED AC RENTAL EQUIPMENT

Water cooled portable rentals may be necessary in areas where floor space is minimal or when an air-cooled unit cannot be ducted properly. Water-cooled rentals use less power but require a water source, chiller, or cooling tower to reject the heat picked-up by the space. Water is never in contact with the air being cooled so humidity levels are reduced like a standard air conditioner.

EQUIPMENT	CAPACITY (BTU'S)	VOLTAGE /PHASE	BREAKER AMPS	NEMA PLUG	DIMENSIONS W x D x H
5WK07	6,300	115	15	5-15P	22.4 x 12 x 17.6
5WK14	10,400	115	15	5-15P	25 x 10.2 x 31.5
OWC/PWC 1211	12,000	115	15	5-15P	20.13 x 13.13 x 34
6WK16BEA1AAA0	16,000	115	15	5-15P	20.6 x 26.4 x 41
5WK18	16,100	208/230/1	15	6-20P	36 x 12.3 x 28.8
CTW-18	18,000	115	15	5-15P	18.9 x 22.5 x 35.9
OWC/PWC 1811	18,000	115	15	5-15P	21.5 x 16 x 45.7
5WK26	23,000	208/230/1	20	6-20P	36 x 12.3 x 28.8
OWC/PWC 2412	23,950	208/230/1	20	6-20P	21.5 x 16 x 45.7
OWC/PWC 3612	36,100	208/230/1	20	6-20P	28.2 x 21.5 x 51
OWC/PWC 3632	36,100	208/230/3	20	L15-20P	28.2 x 21.5 x 51
OWC/PWC 3634	36,100	460/3	20	L16-20P	28.2 x 21.5 x 51
OWC/PWC 6012	60,100	208/230/1	30	6-30P	28.2 x 29.2 x 53.2
OWC/PWC 6032	60,100	208/230/3	30	L15-30P	28.2 x 29.2 x 53.2
OWC/PWC 6034	60,100	460/480/3	20	L16-20P	28.2 x 29.2 x 53.2



PLUG CONFIGURATION



5-15P



5-20P



6-20P




6-30P



6-50P



L15-20P



L15-30P



L16-20P

PH: (224)535-8363
 EMAIL: info@rent-ac.com
 WEBSITE: www.rent-ac.com



COOLING & HEATING RENTAL EQUIPMENT

AIR COOLED HEAT PUMPS

Heat Pump mobile rental units provide optional heating and/or cooling output in a single self-contained package. Heat pumps are great for commercial and industrial environments where there are wide temperature swings year-round. Safe and easy installation with no hot surfaces. Heat pumps provide one of the safest and most efficient forms of supplemental heat.

EQUIPMENT	CAPACITY(BTU'S)		VOLTAGE /PHASE	BREAKER AMPS	NEMA PLUG	DIMENSIONS W x D x H
	COOLING	HEATING				
2OACH1211	11,800	11,000	115/1	15	5-15P	20 x 25 x 38
CLIMATE PRO 12	10,200	9,900	115/1	15	5-15P	21 x 27 x 44
CLIMATE PRO D12	11,450	9,900	115/1	15	5-15P	22 x 27 x 47
2OACH1811	16,800	15,600	115/1	20	5-20P	24 x 30 x 46
CLIMATE PRO 18	14,600	13,700	115/1	20	5-20P	21 x 27 x 49
CLIMATE PRO D18	15,500	13,100	115/1	20	5-20P	22 x 27 x 51
2OACH2412	24,020	22,000	208/230/1	20	6-20P	24 x 30 x 46
2OACH3612	36,050	32,500	208/230/1	30	6-30P	27.5 x 35 x 50.25
2OACH3632	36,050	32,500	208/230/3	30	L15-30P	27.5 x 35 x 50.25
2OACH3634	36,050	32,500	460/3	20	L16-20P	27.5 x 35 x 50.25
2OACH6012	60,100	53,500	208/230/1	50	6-50P	27.5 x 39.5 x 51.8
2OACH6032	60,100	53,500	208/230/3	30	L15-30P	27.5 x 39.5 x 51.8
2OACH6034	60,100	53,500	460/3	20	L16-20P	27.5 x 39.5 x 51.8

